

DECLARATION OF PERFORMANCE

Strength graded structural timber

DoP A

Construction product

Strength graded structural timber that meets the requirements of BS EN 14081-1:2005 +A1:2011. For further or more detailed information on the delivered product, in addition to what is given below, see information on the packaging or in possible accompanying commercial document.

Intended use of the construction product

For load-bearing purposes in construction works designed and for other uses where the strength and stiffness of the structure is essential.

Producer

Company: Nydala Trävaru AB
Address: Nydala
SE 570 03 Vrigstad
Sweden

Telephone: +46 382 - 561900
E-mail: mali@nydalatra.se
Web site: www.nydalatra.se

System of assessment and verification of constancy of performance of the construction product

System 2+.

Certification

The notified body CATG Certification Limited (identification number 1245) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. CATG Certification Limited has issued EC Certificate of Factory Production Control No. 1245 – CPR – 2359.

Declared performance

Performance for machine and visual strength graded structural timber in conformity with the harmonized United Kingdom standard BS EN 14081-1:2005+A1:2011 Timber structures – Strength graded structural timber with rectangular cross section – Part 1: General requirements

Overall performance

Species/species group	WPPA: PCAB gran (<i>Picea abies</i>) och PNSY furu (<i>Pinus sylvestris</i>)
Growth area	NNE Europe (Northern and North Eastern Europe)
Durability	4
Reaction to fire	D-s2, d0
Release of dangerous substances	No dangerous substance to be declared.

Machine strength graded structural timber

Thickness	31 – 110 mm.
Width	60 – 300 mm.
Surface finish	Sawn or planed
Dry or wet graded	Dry graded
Grading machine	Dynagrade Tandem 1b 305
Strength, stiffness and density	According to BS EN 338: TR26, C27, C24 or C16.

That the performance for our construction product mechanically strength graded structural timber is in accordance with the declared performance given above is certified:

Nydala den 2022-05-30

Nydala Trävaru AB


.....

Ingemar Lindman VD